

BlueLife™
PURITY UNCOMPROMISED

THE PROMISE OF 100% PURITY

Unique water purifier with advanced Reverse Osmosis technology and detachable stainless steel storage tank, delivers safe and hygienic drinking water.

Presenting



Removes dissolved impurities like Rust, Pesticides, Arsenic, Fluoride, Lead, Heavy Metals, Bacteria and Virus. It delivers purest and tastiest drinking water with preserved essential natural minerals.



*Design Registered

Toll-free: 1800 599 1234

Key Features

- First of its kind only water purifier with detachable stainless steel storage tank
- Sleek and elegant wall-mounted design best suited for domestic applications
- Purification by Polypropylene Sediment Filter, Silver Impregnated Granular Activated Pre-Carbon filter followed by Reverse Osmosis Purification
- Ultra Violet (UV) Sterilisation (TulipsPlus)
- Removes dissolved impurities like Rust, Pesticides, Arsenic, Fluoride, Lead, Heavy Metals, etc.
- Removes Bacteria and Virus
- 10 liters per hour purification capacity
- Fully automatic
- 9 liters of storage capacity makes purified water available on demand even in the absence of electricity and water supply
- Invisible inlet and reject water connections for enhanced aesthetics
- RoHS-compliant durable faucet



Wall Mounted Design



180° Rotatable Tank



Detachable Tank



Stainless Steel Storage Tank



Technical Specifications

Model	BlueLife™ – Tulips (RO)	BlueLife™ – TulipsPlus (RO+UV)
Filter Cartridges	Polypropylene Sediment Filter, Silver Impregnated Granular Activated Pre-Carbon Filter	Polypropylene Sediment Filter, Silver Impregnated Granular Activated Pre-Carbon Filter followed by Ultra Violet (UV) Sterilisation
RO Membrane	TW30-1812-50/Equivalent	
UV Lamp	Nil	11 Watts
Purification Capacity	10 Liters/Hour***	
Storage Tank	9 Liters, Stainless Steel	
Minimum Inlet Water Pressure	0.3 Kg/cm ²	
Power Supply	24VDC, 2 Amps.	
Input Voltage	90-300V AC, 50Hz	
Average Duty Cycle	1500 Liters/Month Maximum	
Dimensions	W 256 x H 452 x D 392 (mm)	

**Under test conditions

Note: Not recommended for installation at above 2000ppm of feed water.



Due to continuous developments, product specifications may change without notice.

website : www.BlueLife.co.in

Manufactured by : BlueLife TechnoSciences India Private Limited, 1-10-63 & 64, Prajay Corporate House, Chikoti Gardens, Begumpet, Hyderabad - 500 016, India.
Customer Care: 1800 599 1234, +91 40 2776 5099, e_mail: info@BlueLife.co.in

Nearest Contact:

*Conditions Apply